


Main Features

- Design factor 4:1 proof tested and certified
- Ball bearing performs full swivel under load

Certification:


Each unit comes fully certified with a test certificate or an EC Declaration of Conformity stating compliance with the essential health and safety requirements of the Machinery Directive 2006/42/EC, the Supply of Machinery (Safety) Regulations 2008 and Section 6 of the Health and Safety at Work Etc Act 1974.





Technical Data

| Product Code | Capacity (tonne) | For Grade 80 Chain | Dimensions (mm) | | | | | | | N -+ \\\ -: -+ \(\) |
|--------------|---------------------|-----------------------|-----------------|----|----|----|-----|----|----|------------------------|
| | | | Α | В | D | Н | K | Р | T | Net Weight (kg) |
| 8-049N-07 | 2.0 | 7, 8 | 36 | 27 | 12 | 22 | 155 | 26 | 18 | 0.9 |
| 8-049N-10 | 3.15 | 10 | 41 | 37 | 16 | 29 | 189 | 36 | 23 | 1.6 |
| 8-049N-13 | 5.3 | 13 | 46 | 40 | 21 | 35 | 233 | 42 | 28 | 3.4 |
| 8-049N-16 | 8.0 | 16 | 61 | 50 | 22 | 44 | 280 | 50 | 35 | 5.1 |
| 8-049N-20 | 12.5 | 18, 20 | 74 | 82 | 25 | 65 | 356 | 56 | 49 | 9.5 |



Due to our policy of continual product development, dimensions, weights and specifications may change without prior notice.