


G100 Connecting Link

Model No. X-015

Main Features

- Quenched and Tempered Alloy Steel
- At least 25 % greater WLL than traditional G80 products
- Manufactured in accordance with EN 1677- 1 and ASTM A952/A952M
- Certified by DGUV GS-OA-15-05
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured
- Design Factor 4:1
- Fatigue rated to 20,000 cycles at 1.5 times the WLL
- Suitable for use with both Grade 80 and Grade 100 chain



Certification:

Each unit comes fully certified with a test certificate or an EC Declaration of Conformity stating compliance with the essential health and safety requirements of the Machinery Directive 2006/42/EC, the Supply of Machinery (Safety) Regulations 2008 and Section 6 of the Health and Safety at Work Etc Act 1974.

Manufactured and tested in accordance with EN1677-1. All YOKE Lifting points meet or exceed all the requirements of ASME B30.26.

Technical Data

Product Code	Capacity (tonnes)	For Grade 100 Chain (mm)	Dimensions (mm)				Net Weight (kg)
			A	B	D	K	
X-015-06	1.4	6	15	17	7	45	0.08
X-015-07	2.5	7, 8	18	23	9	59	0.20
X-015-10	4.0	10	25	27	11	69	0.30
X-015-13	6.7	13	30	37	16	92	0.70
X-015-16	10.0	16	36	39	19	101	1.20
X-015-20	16.0	20	42	46	23	122	2.10
X-015-22	19.0	22	49	59	24	152	3.50
X-015-26	26.5	26	55	62	30	162	4.80
X-015-32	40.0	32	69	79	36	203	9.00

