

**Hack8 Swivel Sling Hook**

The Hack8 swivel sling hook features a generous hook aperture and bowl, making it a versatile hook type suited for a variety of chain sling applications. It is also fitted with a ball bearing swivel attachment type which allows rotational movement of the hook, even when under load. Manufactured from alloy steel, the Hack8 swivel sling hook delivers an excellent balance between toughness and ductility.

**Standards:** designed and manufactured in accordance with EN1677-1 and suitable for use in chain slings certified to EN818-4.


**Product sizes:** available for chain sizes from 8mm to 20mm and with working load limits from 2.0 tonnes to 12.5 tonnes.

**Temperature:** operational temperature range of - 40°C to + 200°C without reduction in working load limit.

**Material:** alloy steel.

**Testing:** crack detection following heat treatment, and proof load tested to 2.5 times working load limit.

**Safety factor:** 4 : 1.



**Specifications**

PART CODE	CHAIN SIZE mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	BOX QTY.	WLL tonnes	MASS kg
8-H24-08	8	45.0	36.0	13.0	28.5	88.0	20.0	23.0	170.0	208.0	15	2.00	0.95
8-H24-10	10	53.0	42.0	15.5	31.0	105.0	23.0	29.5	207.0	254.0	8	3.15	1.71
8-H24-13	13	63.8	50.0	17.0	40.0	135.0	32.0	38.0	248.0	305.0	6	5.30	3.13
8-H24-16	16	68.0	61.0	21.5	45.0	161.0	37.5	45.0	295.0	367.0	3	8.00	5.44
8-H24-20	20	90.5	74.0	25.0	56.0	194.0	49.0	50.0	356.0	434.0	2	12.50	9.50

### Hack8 Swivel Sling Hook

The Hack8 swivel sling hook features a generous hook aperture and bowl, making it a versatile hook type suited for a variety of chain sling applications. It is also fitted with a ball bearing swivel attachment type which allows rotational movement of the hook, even when under load. Manufactured from alloy steel, the Hack8 swivel sling hook delivers an excellent balance between toughness and ductility.

**Standards:** designed and manufactured in accordance with EN1677-1 and suitable for use in chain slings certified to EN818-4.


**Product sizes:** available for chain sizes from 9/32 - 5/16 inch to 3/4 inch and with working load limits from 4,500 lbs to 28,300 lbs.

**Temperature:** operational temperature range of -40°F to +392°F (-40°C to + 200°C) without reduction in working load limit.

**Material:** alloy steel.

**Testing:** crack detection following heat treatment, and proof load tested to 2.5 times working load limit.

**Safety factor:** 4 : 1.



### Imperial Specifications

PART CODE	CHAIN SIZE inch	A inch	B inch	C inch	D inch	E inch	F inch	G inch	H inch	I inch	BOX QTY.	WLL lbs	MASS lbs
8-H24-08	9/32 - 5/16	1.77	1.42	0.51	1.12	3.46	0.79	0.91	6.69	8.19	15	4500	2.09
8-H24-10	3/8	2.09	1.65	0.61	1.22	4.13	0.91	1.16	8.15	10.00	8	7100	3.77
8-H24-13	1/2	2.51	1.97	0.67	1.57	5.31	1.26	1.50	9.76	12.01	6	12000	6.90
8-H24-16	5/8	2.68	2.40	0.85	1.77	6.34	1.48	1.77	11.61	14.45	3	18100	11.99
8-H24-20	3/4	3.56	2.91	0.98	2.20	7.64	1.93	1.97	14.02	17.09	2	28300	20.94